

TECHNICAL SPECIFICATION

Model	: Turn Table BETT- 36.
Disck Size	: 36" Dia.
Height	: 850 + 50 mm.
Structure with support	: S.S 304.
Speed	: Variable speed
Motor And Gear Box	: Rotomotive
Direction	: Clockwise or Anticlockwise as per required by you
Electrical rating	: 3 phase, 400V 50 Hz supply.



* This machine Image for refernce only

Salient Feature:		
•	Uniform Flow of container.	
•	Fully body constructed by S.S. 304.	
•	Jerk free & noiseless operation.	
•	Variable speed with AC drive.	

OPTIONAL FEATURES:		
	•	Castor Wheel with Lock arrangement.
	•	Extra Tray for loading & unloading of container.

PREREQUISITES:		
Floor Space requirement	: Approximately 1mtr from front & back sides of the machine. Hence, clearance of 1mtr should be added to the actual size of the machine.	
Operator requirement	: Semi Skilled	
Electric supply	: 3Phase electric supply, 400 V, 50Hz Earth & Neutral.	



UTILITY:

- 3 Phase electric supply, 400 V , 50Hz Earth & Neutral.
- Stabilizer will be provided by you to avoid voltage fluctuation.
- All civil work where the machines are to be installed.

TECHNICAL SPECIFICATION

Automatic Powder Filling Machine-BEAPFM-100		
Model	: Automatic Powder Filling Machine-BEAPFM-100	
Container Type	:PET,GLASS,HDPE,PE ETC.	
Speed *	: 50 gram Up to 35 to 40 bottles per minutes	
Conveyor	: 1800mm (L) x 100mm (W) x 850 mm (H) S.S. slat chain Conveyor	
Direction	: Left to Right.	
Power supply	3–Phase 400V, and Earthing 50 Hz AC Supply.	
Change parts	: Auger Screw With Funnel Pipe	

*depends on bottle and cap sizes



MACHINE FEATURES :
Model no. :BEAPFM-100
Machine speed: 50 gram Up to 35 to 40 bottles per minutes
Voltage - 3-Phase, 430V, 50 Hz
Synchronized motor for conveyor and Cylinder
Induction motors make: BONVARIO



Special design of Hopper for more storage capacity
VFD make : Allen Bradley (Made in USA)
Pneumatic Make : Janatics
Synchronized cylinder and conveyor
No bottle sensors optional
Product Material: PET,GLASS,PE.HDPE
Machine size:1800*800*1700 mm

TECHNICAL SPECIFICATION

Automatic Singal Head Screw Capping Machine-BEACM-100	
Model	: Automatic Singal Head Screw Capping Machine-BEACM-100
Container Type	:PET,GLASS,HDPE,PE ETC.
Speed *	: Up to 35 to 40 bottle per min.
Cap Size	: 20-50 mm
Conveyor	: 2000 mm (L) x 100mm (W) x 850 mm (H) S.S. slat chain Conveyor
Direction	: Left to Right.
Power supply	3-Phase 400V, and Earthing 50 Hz AC Supply.
Change parts	: Star wheel <mark>, G</mark> uide

*depends on bottle and cap sizes



MACHINE FEATURES:

	Model no. :BEACM-50
•	Machine speed: Up to 35to 40 bottle/min
	Voltage - 3-Phase, 430V, 50 Hz
	Synchronized motor for conveyor and star wheel
	Bottle jam, Machine stop with Indication
	Special design of Hopper for more storage capacity



·	Induction motors make: ROTOMOTIVE
	VFD make : Allen Bradley (Made in USA)
	Pneumatic Make : Janatics
	Switch gear Make: Schneider Electric
	Synchronized star wheel and conveyor
	No bottle sensors optional
	Product Material: PET,GLASS,PE.HDPE
	Machine size:2000*1100*1200 mm
	Cap Size: 20 to 50 mm

ANNEXURE-A	
TECHNICAL SPECIFICATION	
Automatic Induction Sealing Machine	
Model	Automatic Induction Sealing Machine-BEIM-100
Cap size :	: Cap Dia : 20 MM TO 120 mm
Bottle Sizes**	:From 500 ml to 5000 ml
Line Speed *	: Maximum 13.5 mtr per minute
Machine Dimension	: 2 <mark>0</mark> 00*600*1500 mm
Induction Sealer Dimension	6 <mark>5</mark> 0*650*1300 mm
Direction	: Left to Right.
Power Supply	1-Phase,230 V, 50 Hz
** With help of Head Moveme	ent



	MACHINE FEATURES :
	Automatic Induction Sealing Machine-BEIM-100
	Model no. : BEIM-100
	Machine speed: Up to 13.5 Meter per minute
	Machine weight : 175 Kg
	Easy to use membrane switches
	Single body nOn conveyor system
	Suitable for use in Cosmetics, Pharmaceuticals, Pesticides, Butter Milk, Edible Oil,
Milk,	Honey, Lubricants etc.
	Imported Motors and Gears set(Italian Technology)
	Temper evident sealing



Continues type sealing
Over current Protection
Over temperature
Imported VFDs from Allen breadley make (USA)

	PREREQUISITES
Floor space required	: Approx.1 Mtr Floor space needed from all side of
	machines, Hence 1 Mtr from all side will be added to
	actual size of Machine
Operator Required	: 1 Skilled/Semi skilled Operator.
Electric Supply	: 1-Phase,230V AC,50 Hz.

	ESSENTIAL:		
	Container, Capsules, Cap and Label roll Should be of Good Quality.		
	Operator should understand the working of machine properly.		
	UTILITY		
	1-Phase electric supply		
	Stabilizer will be provided by you to avoid voltage fluctuation.		
	All civil works where the machine is to be installed.		

ANNEXURE-A TECHNICAL SPECIFICATION

: Automatic Sticker labeling Machine-BEASL-100(150 mm
Sticker)
: PET,GLASS,HDPE,PE ETC.
: Advance Stepper motor Control System
: Up to 80bottle per min.
: 150 mm maximum
: 290 mm Maximum
: 2000 mm (L) x 100mm (W) x 850 mm (H) S.S. slat chain
Conveyor
: Left to Right.
: Round Bottle
: 1 –Phase 220 V, and Earthing 60 Hz AC Supply.
: Wrap-Around Unit and Support Foam Plate for Round Bottles

^{*}depends on bottle and cap sizes





MACHINE FEATURES:

- Stepper Motor control system
- Programmed Controller with advance Electronics
- Product sensor for product counter
- Bottle Separator Motor
- No bottles, No labels arrangements
- Sensor make : LEUZE
- Induction motors make: Bonvario (Made in Italy)
- VFD make : Allen Bradley (USA)
- Pneumatic Make : Janatics
- Product size: 10 ml to 1000 ml
- Product Material: PET,GLASS,PE,HDPE,ALUMINUM ,ETC.
- Machine size:2000*600*2000 mm
- Sticker roll dia: 300 mm
- Sticker roll height: 150 mm
- Suitable for printing devices.



OPTIONAL FEATURES

- Online Printing
- Servo Motor instead of Stepper motor
- Online inspection and rejection system
- Tower light : Indicates process of Machine
- We Also Provide Customize solution for Stickering Application

For Abelard Network Pvt. Ltd.

INDIA E DELATA